GENSURE E-2200X FUEL CELL Power for Grid-Support Stationary Applications

Plug Power's GenSure E-2200x[™] hydrogen fuel cell is optimized for grid-support and high duty cycle customer applications. It offers robust reliability, providing extended runtime for critical equipment. Unlike traditional generator technologies, which can be unpredictable and maintenanceheavy, GenSure systems deliver reliable, simple-to-maintain power over the widest range of operating environments. Multiple systems may be combined for higher power applications. Plug Power's GenSure fuel cell solutions provide scalable, clean, cost-effective performance while offering an unparalleled degree of flexibility in addressing both space and runtime constraints of customer locations, with indoor shelter and outdoor cabinet options.

Proven. Rugged. Reliable. Clean. Plug Power has installed more than 3,800 GenSure fuel cells at customer sites across the United States and 36 other countries. With more than 100 million installed hours of site power protection, GenSure products are field-proven through snow and ice storms, hurricanes and other severe weather events. Because the only emissions are warm air and a small amount of water, the E-2200x is exempt from the most stringent air quality standards and is a valuable component of corporate sustainability efforts.



Powering Your Possibilities.

ROBUST, RELIABLE POWER

If your utility grid is unreliable or non-existent, your power solution had better be ready to perform. Plug Power's GenSure E-2200x fuel cells are optimized for high duty cycle, grid-support applications. Self-diagnostics and an auto-exercise program maintain fuel cell performance levels.

SCALABLE FOR HIGHER CAPACITY APPLICATIONS

GenSure E-2200x fuel cells may be used solo for power requirements under 2,200W or in multiples for larger power requirements or N+1 redundancy. Flexible outdoor cabinet options allow customers to purchase the amount of power they need now and upgrade if requirements change in the future.

ENVIRONMENTALLY-HARDENED

Power solutions need to perform wherever your equipment is located. Plug Power's GenSure fuel cells perform in hot and cold, humid and arid environments. Certification testing has confirmed their capabilities in wind-driven rain, brush fire and earthquake conditions. Most importantly, these fuel cells perform reliably in real world conditions.



COST-EFFECTIVE

Required fuel cell maintenance is limited to an annual air filter exchange. The GenSure E-2200x is covered by an industry-leading warranty and fuel cell health and fuel levels may be remotely monitored. Simple maintenance and fewer site visits mean up to 84% lower operational costs when compared to combustion generators. Clean, zero-emissions operation means not having to address fuel spill containment and air quality reporting requirements.

PRODUCT SPECIFICATIONS		
PHYSICAL	DIMENSIONS (W X D X H)	21.34" x 24" x 14" / 54.2cm x 61cm x 35.6cm
	WEIGHT	113 lbs / 52.4 kg
	MOUNTING	23" rack mount
PERFORMANCE	RATED POWER	2,200W (93A @ 24V / 46.5A @ 48V)
	DC VOLTAGE	24 / 48V nominal
OPERATION	AMBIENT TEMP	23°F to 122°F / -5°C to 50°C (Optional -40°F to 122°F / -40°C to 50°C in hardened outdoor cabinet)
	RELATIVE HUMIDITY	0-95% non-condensing
	ALTITUDE	-197 ft to 13,800 ft / -60m to 4,206m
	LOCATION	Indoors or hardened outdoor cabinet
EMISSIONS	WATER	Max 25mL / kWh (primarily vapor)
	NOISE	58.6dBA @ 23ft (7m) / 72dBA @ 4.9ft (1.5m)
MONITORING/CONTROL	REMOTE	System configuration & status / Historical & operational data
	COMMUNICATIONS	Standard: USB / Dry contact / Ethernet / SNMP / Web interface Optional: Wireless modem - CDMA / GSM / Ethernet switch
FUEL: STANDARD INDUSTRIAL-GRADE HYDROGEN (99.95%)		
	SUPPLY PRESSURE TO UNIT	8 to 12 psig / 55.1 to 82.8 KPag / 0.55 bar to 0.83 bar
	CONSUMPTION	28 slpm @ 2,200W
	H ₂ STORAGE CAPACITY	n/a (multiple fueling solutions available separately)

Specifications subject to change without notice. Information based on standard products working under normal operating conditions.

Corporate Headquarters

968 Albany Shaker Road Latham, NY 12110 518.738.0320 West Coast 15913 E. Euclid Ave. Spokane, WA 99216 509.228.6500



PLUGPOWER.COM gensure@plugpower.com

122015