THE 1MW ELECTROLYZER Best-in-class stack life expectancy of 80,000 hours

The GenFuel 1MW proton exchange membrane (PEM) electrolyzer system provides up to 1MW of on-site hydrogen for markets including heavy industry, e-mobility and energy storage. Electrolyzers generate hydrogen from water using electricity and a special membrane and "green" hydrogen is generated by using renewable energy inputs, such as solar or wind power. The 1MW product is based on 47+ years of experience in design, production and sales of electrolyzer stacks and integrated products.

- Flexible & Scalable to meet a wide array of performance requirements
- Robust & Dependable, providing industry-leading performance
- Turnkey 1MW containerized system for simple siting and installation
- Environmentally-friendly, with lowest O&M in its class
- World class lifetimes with stable operating voltages





ADAPTABLE & MODULAR SOLUTIONS SUPPORT INDUSTRY EXPANSION

 \mathbf{I}

1.1

POWER CONDITIONER I I

1.1

1.1

1.1

WATER

TREATMENT I I GENERATION

GAS DRYING & CLEANING



THE GENFUEL 1MW ELECTROLYZER SYSTEM IS A MODULAR **BUILDING BLOCK TO SUPPORT YOUR ENERGY STORAGE,** HYDROGEN FUELING STATION AND INDUSTRIAL NEEDS.

1.1

PRODUCT SPECIFICATIONS (SYSTEM)	
SPECIFICATION	RATING
INPUT	
ELECTRICAL INPUT	480VAC, 60Hz (USA) / 400VAC, 50Hz (EU)
BALANCE OF PLANT	
WATER	Feed: Maximum 411 kg/hr @ 2barg, potable water
PHYSICAL	
DIMENSIONS (W X H X L)	8' x 8' x 40' container
WEIGHT	35 tons
AMBIENT TEMPERATURE	-20°C to +40°C
PERFORMANCE	
HYDROGEN PRODUCTION	200Nm3/hr / 18 kg/hr
HYDROGEN PURITY	99.999% with H2 dryer*
HYDROGEN PRESSURE	40 barg
STARTUP TIME	30 seconds (warm start) / 5 minutes (cold start)
EFFICIENCY	Up to 84%
LIFE EXPECTANCY	Stack: 80,000 hours
COMMUNICATION	24/7 data acquisition and remote monitoring
CERTIFICATIONS	Compliant to ISO 22734, NFPA 2, CRN, CE

Product specifications are subject to change without notice.

Corporate Headquarters 968 Albany Shaker Road Latham, NY 12110 518.738.0320



^{*99.9%} without H2 dryer